

Pressure regulator MS2-LR-M5-D6-AR-BAR-B

Part number: 8086628

FESTO



 General operating condition

Data sheet

| Feature | Value |
|---|---|
| Size | 2 |
| Series | MS |
| Actuator lock | Rotary knob with detent |
| Mounting position | optional |
| Design | Directly actuated diaphragm regulator |
| Controller function | Output pressure constant With secondary venting With return flow function |
| Symbol | 00991558 |
| Displayable units | bar psi |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge |
| Operating pressure | 0.1 MPa ... 1 MPa |
| Operating pressure | 1 bar ... 10 bar |
| Pressure regulation range | 0.5 bar ... 7 bar |
| Max. pressure hysteresis | 0.025 MPa |
| Max. pressure hysteresis | 0.25 bar |
| Max. pressure hysteresis | 3.625 psi |
| Standard nominal flow rate (standardised to DIN 1343) | 170 l/min |
| Operating medium | Compressed air to ISO 8573-1:2010 [7:4:4] Inert gases |
| Corrosion resistance class CRC | 1 - Low corrosion stress |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Cleanroom class | Class 4 according to ISO 14644-1 |
| Storage temperature | -5 °C ... 50 °C |
| Media temperature | -5 °C ... 50 °C |
| Ambient temperature | -5 °C ... 50 °C |
| Product weight | 38.6 g |
| Type of mounting | Either: Front panel mounting In-line installation With accessories |
| Pneumatic connection, port 1 | M5 |
| Pneumatic connection, port 2 | M5 |
| Note on materials | RoHS-compliant |
| Material underneath cover | PA |

| Feature | Value |
|----------------------|--------------------------------|
| Material seals | NBR |
| Material rotary knob | POM |
| Material spring | High-alloy steel |
| Material housing | PA-reinforced |
| Material membrane | NBR |
| Material valve stem | Wrought aluminium alloy NBR |