PAR�FIT™


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

Creation Date:	17-12-2018
Datasheet No:	DS026W
Parker Part No:	PR2798Q
OEM:	Pall
OEM Part No:	HC8300FKN16H&Z

Product Dimensions

A (mm)	153.0	(inch)	6.02
B (mm)	105.0	(inch)	4.13
C (mm)	105.0	(inch)	4.13
D (mm)	153.0	(inch)	6.02
E (mm)	425.0	(inch)	16.73





Construction Materials

Seal(s):	FPM: Fluoroelastomer
Top Endcap:	Mild steel tin plated
Bottom Endcap:	Mild steel tin plated
Inner Support Cylinder:	Mild steel tin plated
Filter Media:	Multilayer fibreglass with coated mesh on both sides

Calculated Performance Criteria

Differential Pressure (∆p):	0.28 bar @ 500 l/min		
Tested to ISO3968 @ 32 cSt	4.06 psi @ 109.98 gp		
Efficiency: >Beta 200 @ 6 microns & greater >Beta 1000 @ 7 microns & greater			
Minimum Collapse Pressure:	>10 bar		
Tested to ISO2941	>145 psi		
Dirt Holding Capacity acc. to ISO16889 177.0 gram @ 5 bar terminal pressure drop 177.0 gram @ 73 psi terminal pressure drop			

ENGINEERING YOUR SUCCESS.